



PERRY JOHNSON LABORATORY ACCREDITATION, INC.

Certificate of Accreditation

Perry Johnson Laboratory Accreditation, Inc. has assessed the Laboratory of:

***Nissenken Quality Evaluation Center
Chubu Laboratory – Testing Center
7 Aza Gohigashi, Shinkanbe, Imaise-cho, Ichinomiya, Aichi 491-0052***

*(Hereinafter called the Organization) and hereby declares that Organization is accredited
in accordance with the recognized International Standard:*

ISO/IEC 17025:2017

This accreditation demonstrates technical competence for a defined scope and the
operation of a laboratory quality management system
(as outlined by the joint ISO-ILAC-IAF Communiqué dated April 2017):

***Flammability testing
(As detailed in the supplement)***

Accreditation claims for such testing and/or calibration services shall only be made from addresses referenced within this certificate. This Accreditation is granted subject to the system rules governing the Accreditation referred to above, and the Organization hereby covenants with the Accreditation body's duty to observe and comply with the said rules.

For PJLA:

Tracy Szerszen
President

Initial Accreditation Date:

September 3, 2020

Issue Date:

September 3, 2020

Expiration Date:

October 31, 2022

Accreditation No.:

107211

Certificate No.:

L20-518

Perry Johnson Laboratory
Accreditation, Inc. (PJLA)
755 W. Big Beaver, Suite 1325
Troy, Michigan 48084

*The validity of this certificate is maintained through ongoing assessments based on a
continuous accreditation cycle. The validity of this certificate should be
confirmed through the PJLA website: www.pjlab.com*



Certificate of Accreditation: Supplement

Nissenken Quality Evaluation Center Chubu Laboratory – Testing Center

7 Aza Gohigashi, Shinkanbe, Imaise-cho, Ichinomiya, Aichi 491-0052
Contact Name: Satoshi Yokota Phone: 0586-45-6477

Accreditation is granted to the facility to perform the following testing:

FIELD OF TEST	ITEMS, MATERIALS OR PRODUCTS TESTED	SPECIFIC TESTS OR PROPERTIES MEASURED	SPECIFICATION, STANDARD METHOD OR TECHNIQUE USED	RANGE (WHERE APPROPRIATE) AND DETECTION LIMIT
Thermodynamic ^F	Interior Materials used in road vehicles, and tractors and machinery for agriculture and forestry (For example; Fabric of car seats)	Flammability testing: Burning distance Burning time Burning velocity	“Detailed Regulation for Operation of Flammability Test Methods” (NSK-025-ISO3795) On the basis of: ISO 3795 (Normative references: ISO 2768-1) and JIS D 1201	Burning distance: 2 mm to 254 mm Burning time: 0.5 s Burning velocity: 4 mm/s

1. The presence of a superscript F means that the laboratory performs testing of the indicated parameter at its fixed location. Example: Outside Micrometer^F would mean that the laboratory performs this testing at its fixed location.

