

Test Request Form 【General】

Reception date: _____

Request form No. _____

Company Name _____

Desired delivery date

Nissenken Quality Evaluation Center

Department _____

Person in charge _____

Address _____

/

Request the issuance of test report in the below test order

TEL _____

FAX _____

Send • Pick up

Be sure to fill out the area with bold frame. In addition, if there are special items, write them in the remarks column.

Item name :		c / # (color name) :		Fiber contents :		Number of the report copies		
Item No. :						Japanese		
		Item		Specified by requester • Required items		Fabric test • Garment test		
Addressee for report :				Applicable standard				
				Buyer				
Addressee for billing :				Material manufacturer				
Test items		Test standard		Qty.		Product classification		
C o l o r f a s t n e s s	Light resistance		Carbon • Xenon Exposure grade				Sample • Mass production	
	Washing		A-1 • A-2 Detergent (Neutral • Synthetic) Solution staining				Color scheme	
	Water						Yes • No	
	Perspiration		Acid • Alkaline				Brand	
	Rubbing (Dry • Wet)		Type II • Type I (Crockmeter)				Season	
	Dry cleaning		Perchloroethylene • Petroleum based Solution staining				Pass/Fail judgement	
	Bleeding		Daimaru method • Petroleum based / As is • Addition				Yes • No	
	Chlorinated water		Method A • Method B				Garment cut, tear etc.	
	Sublimation						Acceptable • Not acceptable	
	Oxygen bleach						Return remaining samples	
Perspiration to light		Method A Method B Acid • Alkaline / ATTS Acid • Alkaline				Yes • No		
C i D h o m e n a n g l e	Immersion method		Method C • Method D				Return product	
	Home electric washer		C3N • C3M • C3G • C4N • C4M • C4G • C4H				Yes • No	
	Drying		J-1 • J-2				Return Colorfastness • Pilling samples	
P r o s p e c t i v e	Press		H-1 • H-2 • H-3				Yes • No	
	Tensile strength		Strip method • Grab method				Return dimension • slippage samples	
	Tearing strength		Pendulum method • Single tongue method				Yes • No	
	Bursting strength		Mullen type method					
	Slippage resistance		Method B (49.0N • 117.7N)					
	Abrasion strength		Flat surface • Folded line • Uniform • Martindale					
	Pilling		ICI (3 • 5 • 10 hours)					
F u n c t i o n a l	Snag		Method A (Mace method) • Method D-1					
	Water repellency		Initial • After washing • After drying					
	Water resistance		Low water pressure method • High water pressure method					
	Water absorbency		Drip method • Byrek method • Sedimentation method					
	Quick-drying property							
	Free formaldehyde		Infants • General / Fabric • Garment					
	UV shielding rate		label % • UPF value					
	Mixture rate							
G a r m e n t	Animal hair mixture rate							
	Appearance inspection		Appearance • Sewing • Label					
	Laundering resistance		C3N • C3M • C3G • C4N • C4M • C4G • C4H					
			Flat dry • Tumble • Line dry					
			Synthetic • No fluorescence • Neutral					
Dry cleaning resistance				Tumble dry		Natural dry		
		Perchloroethylene		Method D6736 • Method P1 • Method P2				
		Petroleum solvents		Method D7736 • Method F1 • Method F2		D7746		

If garment inspection is needed, confirm if the following is attached:
• Hang tag

Remarks column

Example

Please fill out the area with bold frame.
 ※Please be sure to fill out the part in red.
 ※Please fill out as much as you can for the blue part.

Test Request Form 【General】

Reception date: _____

Request form No. _____

Company Name	Nissenken	
Department	Quality Control	Person in charge Nissen Taro 様
Address	〒111-0051 Kuramae 2-16-11 Taito-ku Tokyo	
TEL	03-3861-2341	FAX 03-3861-4280

Desired delivery date

Nissenken Quality Evaluation Center

Request the issuance of test report in the

/

Send・Pick up

Be sure to fill out the area with bold frame. In addition, if there are special items, write them in the remarks column.

Item name :	c / # (color name) :	Fiber contents :	Number of the report copies Japanese 1 English
Item No. : 123-456	010 black・100 white	80% Cotton 20% Polyester	

Item	T-shirt	Specified by requester	Required items	Fabric test	Garment test
------	---------	------------------------	----------------	-------------	--------------

Addressee for report :	Applicable standard	Nissenken
------------------------	---------------------	-----------

Addressee for billing :	Buyer	
-------------------------	-------	--

Material manufacturer	Product classification	Sample ・ Mass production
-----------------------	------------------------	--------------------------

Color scheme	Yes ・ No
--------------	----------

Brand	Season
-------	--------

Pass/Fail judgement	Yes ・ No
---------------------	----------

Garment cut, tear, etc.	Acceptable	Not acceptable
-------------------------	------------	----------------

Return remaining samples	Yes ・ No
--------------------------	----------

Return product	Yes ・ No
----------------	----------

Return Colorfastness ・Pilling samples	Yes ・ No
---------------------------------------	----------

Return dimension ・ slippage samples	Yes ・ No
-------------------------------------	----------

Immersion method	Method C ・ Method D
------------------	---------------------

Home electric washer	C3N ・ C3M ・ C3G ・ C4N ・ C4M ・ C4G ・ C4H
----------------------	---

Drying	J-1 ・ J-2
--------	-----------

Press	H-1 ・ H-2 ・ H-3
-------	-----------------

Tensile strength	Strip method ・ Grab method
------------------	----------------------------

Tearing strength	Pendulum method ・ Single tongue method
------------------	--

Bursting strength	Mullen type method
-------------------	--------------------

Slippage resistance	Method B (49.0N ・ 117.7N)
---------------------	-----------------------------

Abrasion strength	Flat surface ・ Folded line ・ Uniform ・Martindale
-------------------	--

Pilling	ICI (3 ・ 5 ・ 10 hours)
---------	--------------------------

Snag	Method A (Mace method) ・ Method D-1
------	-------------------------------------

Water repellency	Initial ・ After washing ・ After drying
------------------	--

Water resistance	Low water pressure method ・ High water pressure method
------------------	--

Water absorbency	Drip method ・ Byrek method ・ Sedimentation method
------------------	---

Quick-drying property	
-----------------------	--

Free formaldehyde	Infants ・ General / Fabric ・ Garment
-------------------	--------------------------------------

UV shielding rate	label % ・ UPF value
-------------------	---------------------

Mixture rate	
--------------	--

Animal hair mixture rate	
--------------------------	--

Appearance inspection	Appearance ・ Sewing ・ Label
-----------------------	-----------------------------

Laundering resistance	C3N ・ C3M ・ C3G ・ C4N ・ C4M ・ C4G ・ C4H
-----------------------	---

Dry cleaning resistance	Flat dry ・ Tumble ・ Line dry
-------------------------	------------------------------

	Synthetic ・ No fluorescence ・ Neutral
--	---------------------------------------

	Tumble dry	Natural dry
--	------------	-------------

Perchloroethylene	Method D6736・Method P1・Method P2	
-------------------	----------------------------------	--

Petroleum solvents	Method D7736・Method F1・Method F2	D7746
--------------------	----------------------------------	-------

Remarks column

Please put a circle if there are specified items

If garment inspection is needed, confirm if the following is attached:
 ・ Hang tag
 ・ Sewn symbol care label

1 Fill out all the information [Address・TEL・FAX・Company・Department・Person in charge]

2 【Item name】 Please fill it out if available

3 【Item No.】 Please fill out all parts

4 【c/#(Color name)】 Please fill out all parts

5 【Item】 Please fill out all parts

6 【Fiber content】 Please fill out as much as you can

7 【Number of report copies】 Please be sure to fill out how many copies are needed for Japanese & English

8 【Addressee of report & invoice】 Please fill in each

9 【Applicable standard】 Please fill out the applicable standard

10 【Garment cut,tear, etc.】 ※Please fill it out if it is a garment